

## DC706

Flex chrome double interlock.

L 150 cm anti-twist

1/2" F x 1/2" F



### CONSTRUCTION SPECIFICATIONS

- Hose made up of:
  - non-toxic PVC substrate;
  - external protection in BRASS with DOUBLE CHROME-PLATED SEALING;
  - brass fittings with AISI 304 stainless steel liner
  - 1/2" gaskets in non-toxic EDPM rubber

### TECHNICAL SPECIFICATIONS

- Maximum working temperature: 50 °C
- Maximum working pressure: 3 Bar (bursting pressure 8 Bar)
- Flow: 23 l/min. to 3 bar
- Bend radius: 45 mm

Complete with anti-rotation connection system with seal assembled with EPDM:

A SIDE: 36 mm shiny smooth cone and anti-twist system with assembled seal

B SIDE: brass chrome-plated smooth cap covering the pinched sleeve, with assembled seal.



### DIMENSIONAL SPECIFICATIONS

- Hose length: 150 cm
- Connections: G 1/2" F x G 1/2" F
- Ø internal hose: 9 mm
- Ø external hose: 14,8 mm

WE RECOMMEND CARRYING OUT MAINTENANCE ON NOZZLES AND CHROME PARTS USING A SOFT CLOTH DAMPENED WITH A LITTLE WATER. DO NOT USE ABRASIVES OR ANTI-LIMESCALE DETERGENTS.

### PRODUCTION RANGE

Art.	Code	Finishing
DC706	4180351	chrome